





Bodenkanalheizung Kampmann Katherm NK - Natürliche Konvektion

Pumpenwarmwasser (PWW) 75/65 °C bzw. Niedertemperaturbetrieb (NT) mit PWW 50/40 °C möglich

Kanallänge in mm	Wärmeleistung Watt PWW 75/ 65°C, 20 °C Lufteintritt	Wärmeleistung Watt PWW 55/ 45°C, 20 °C Lufteintritt	Preis inkl. 19% MwSt.	
Kanalbreite: 182 mm, Kanalhöhe 92 mm				
	850	125	67	297,50 €
	1250	214	114	389,13 €
	1750	325	173	503,37 €
	2250	436	232	623,56 €
	2750	547	290	736,61 €
	3250	658	349	852,04 €
	3750	769	408	969,85 €
	4250	880	467	1.085,28 €
	4750	991	526	1.203,09 €
	5000	1047	555	1.262,59 €
Kanalbreite: 272 mm, Kanalhöhe 92 mm				
	850	182	98	397,46 €
	1250	306	165	522,41 €
	1750	462	248	673,54 €
	2250	617	332	825,86 €
	2750	773	415	978,18 €
	3250	928	499	1.130,50 €
	3750	1084	583	1.282,82 €
	4250	1239	666	1.437,52 €
	4750	1395	750	1.582,70 €
	5000	1473	792	1.655,29 €
Kanalbreite: 340 mm, Kanalhöhe 92 mm				
	850	245	129	452,20 €
	1250	412	218	587,86 €
	1750	621	329	756,84 €
	2250	830	439	927,01 €
	2750	1039	550	1.097,18 €
	3250	1248	661	1.264,97 €
	3750	1457	771	1.435,14 €
	4250	1666	882	1.604,12 €
	4750	1875	992	1.771,91 €
	5000	1979	1048	1.856,40 €
Kanalbreite: 400 mm, Kanalhöhe 92 mm				
	850	302	158	543,83 €
	1250	509	266	702,10 €
	1750	768	401	904,40 €
	2250	1026	536	1.104,32 €
	2750	1285	671	1.304,24 €
	3250	1543	806	1.504,16 €
	3750	1802	941	1.706,46 €
	4250	2060	1076	1.905,19 €
	4750	2319	1211	2.107,49 €
	5000	2448	1279	2.209,83 €

Weitere Roll- bzw. Linear-Rost-Ausführungen auf Anfrage.

Unverbindliche Preisempfehlung, Stand 2009